

[RP-1700 series]

RP-17 - - - P / R

No.	Method of mounting	Shaft shape	No.	Input power supply	Output phase	No.	Signal output method	No.	Connection type	Approved standard	No.	Oil Seal
1	Bottom-mount Type	D-cut	1	AC 100 to 240 V	A & B phases	T	Totem pole	T	Terminal Strip	PSE	0	Not provided
2		key groove	2	DC 12 to 24 V		O	Open collector	C	Standard Connector	PSE	1	Provided
3	Flange-mount Type	D-cut	3	AC 100 to 240 V	A,B & Z phases	C	Collector	1	Terminal Strip	TUV conformed		
4		key groove	4	DC 12 to 24 V		L	Line driver	2	Standard Connector	TUV conformed		
								3	Terminal Strip	UL conformed		
								4	Standard Connector	UL conformed		

[RP series other than RP-1700 series]

RP - - - P / R

Item selected		Power Rating		Zero Mark	Signal output	Connection type			Oil Seal	
		AC	DC		Open collector	Terminal Strip	Standard Connector	Direct Cable	Not provided	Provided
		A	D	Z	O	T	C	N	0	1
Ultra-Compact Type	SP-405ZA		●	●	○			●	●	
Multi-use Type	RP-432Z		●	●			●		●	

Items marked “●” : Standard specification

Items marked “○” : Optional specification, can be manufactured upon request.